

The LifeDesk: LD1 AB+

Key Features

Height range:
22" to 51" plus top

Weight Capacity:
175 pounds

Travel Speed:
1.5" per second

Max Top Size:
Corner: 24" x 36" x 36" x 24"
and Rectangle: 24" x 48"



SPECIFICATIONS

Height Range	22" to 51" (Plus Top) (Height-extender brackets included)
Weight Capacity	175 pounds
Travel Speed	1.5" per Second
Maximum Top Size	Corner Surface: 24" x 42" x 42" x 24" Rectangle Surface: 24" x 48"
Foot	23.6" or 27.5"
Color	Black RAL 9005 or Silver RAL 9006
Standard	CE
ISO 9001 Certified	Quality
ISO 14001 Certified	Environment
Manufacturing Practices	Toyota Production System and 5S
Load Capacity Push (N)	800
Input (VDC)	24
Overload Protection	Integrated in appropriate Control-Box
Duty Cycle	10%, max, 2min. continuous use
Tube Material	Steel
Operating Temperature	+5°C to +40°C

CONTROL BOX SPECIFICATIONS

Number of Actuator Outputs		1
Output Voltage	(VDC)	31
Input Voltage	(VAC)	110 or 230
Transformer Power	(watts)	200/360
Actuator Plugs		Straight cable
Hand control Plugs		RJ straight cable
Power draw		<0.3W in stand-by (Up to 2.5 amp draw depending on load)
Power plug		Can be specified per country's needs
Color		Black
Duty Cycle		10% max, 2 min. continuous use
Overload Protection		For all channels, single-extra protected
Ambient Temperature		+5°C to +40°C
Standard		UL60601-1 / CE

